MACHINE SPECIFICATIONS

Specifications	Descriptions
Model	SE-1000
Supported users	Foreign tourists and overseas returnees. Optionally, ID document verification device can be added for the KYC purposes
Installation location	Indoors (places not exposed to direct sunlight)
Operating conditions	Unmanned/Manned
Transaction method	Cash (foreign currencies, local currency of the installation country)
Communication with servers	Both wired or wireless connection
External dimensions	1,510mm(H) ×450mm(W) ×500mm(D) (Excluding protrusions)
Weight	210 kg
Color	Two-tone (grey and ivory)
Audio	Built-in speakers
Built-in camera resolution	1.3 Mega Pixels (2 cameras)
Power input	AC100V ±10% 50Hz/60Hz (Transformer - option)
Power consumption	90W
Input power plug	NEMA 5-15
Operating temperature range	10~32°C
Operating humidity range	30~85% (no condensation)
Storage temperature range	0~45°C
Storage humidity range	20~90% (no condensation)
Installation structure	Installation plate/Anchor installation
Operational/maintenance side	Front-access maintenance
Lifespan	Five (5) years

KINGTON

Automated Business Systems

KINGTON CO., LTD.

Taiwan office: 5F, No. 194, Sec. 3, Datong Road, Xizhi District, New Taipei City, Taiwan Tel: +886-286626882; kt@kington.com.tw

Tokyo office: Yakult Honsha Building 9F, 1-1-19, Higashi Shimbashi, Minato-ku, Tokyo, 105-0021, Japan. Mobile: +886-939267800

Cebu Office: Unit 23W, Solinea Tower 1, Cardinal Rosales Ave, Cebu City, 6000 Cebu, Philippines Mobile: +63 09260622260

IIONS			
		Specifications	Descriptions
		Model	
	note Deposit U	Supported users	120 countries (select up to 12 currencies- 85 denominations)
		deposit method	Both sides, short edge, 4 directions/1 sheet
		Number of storable bills	1,200 bills
	_	Retrieval method	Cassette type (Lock is optional)
١		Model	
	Jnit	Supported users	Various foreign currency banknotes *Polymer banknotes need verification
		Payout method	Shutter type (Longitudinal)
	sing l	Number of storable bills	1,000 bills /per cassette
	Banknote Dispensing Unit	Replenishment method	Cassette type
		Number of payout bills	Up to 50 bills/transaction
		Payout processing speed	3 bills/sec
		Rejection function	Payout error reject
		Number of cassettes	Standard: 2 cassettes, Maximum: 3 cassettes
		Supported coins	Various foreign currency coins
	Coin Dispensing Unit	Storage capacity	Loading cassette: 1,000 Coins
			Collection vault : 4,000 Coins *The above figures may vary depending on the size of the coin
		Replenishment method	Cassette type
		Payout processing speed	>6 coins/second (per denomination)
		Coin retrieval mechanism	Coin retrieval mechanism + coin retrival safe box
	Unit	Display	15 inches wide TFT-LCD module
	Operating Unit	Operation method	Touch panel (capacitive type)
	Authentication Device	Passport reader	OCR passport reader

CE