

AUTOMATIC BANDING MACHINE

KT-WIIN



**Superior Performance for Automatic Banding
Up to 31pcs/min. Handles both 100 & 1000notes
One single machine for all your banding needs!**



Specification	Sealing Technology	Heating & pressing sticking
	Warm up time	No warm up time required, switch on the power ready to start
	Bundling Tension	Variable adjustment from soft to strong, suit to bundled material
	Max Bundling Force	60N, can be customized super bundling force for firmly banding
	Bundling Capacity	Max: 444 (W) x 212 (H) mm; Min: 40 (W) x 10 (H) mm
	Bundling Speed	30~31 bumbles/minute (1,860 bundle/hour)
	Start Mode	1. Automatic Active, 2. Start Button, 3. Foot Switch (Option)
	Power Supply	Selectable AC110 or AC220V 50/60Hz (Universal Standard)
	Power Consumption	AC 110V 60 Hz or 220V 50Hz: Max.260W
	Dimension	Floorstand: 585 (W) x 486 (D) x 1105 (H) mm
	Weight	N.W.: 65 kgs ; G.W.: 65.5 kgs ; Wooden Box Packed: 80kg.
	Available Tape Material	Both Paper Tape and Transparent Plastic film Tape
	Available Tape Spec.	Width: 30mm, Customized: 20/25/40mm; Length: 600M



KINGTON
Automated Business Systems

KINGTON CO., LTD.

5F, No. 194, Sec. 3, Datong Road,
Xizhi District, New Taipei City, Taiwan
TEL / FAX : 886-2-8662-6882

For more information, contact:

